



TECHNICAL DATA		STD	
EXTERNAL DIMENSIONS			
width		590 mm	
depth		600 mm	
height		850 mm	
WEIGHT			
		56.5 kg	
VOLTAGE			
		400V 3N 50Hz	
POWER REQUIRED			
		5150 W	
WATER HARDNESS			
		2-8 °F	
INLET WATER PRESSURE			
		200-400 kPa	
CROCKERY DIMENSIONS			
plates diameter		345 mm	
dishes max. height		320 mm	
RACK DIMENSIONS			
		500X500 mm	
RACK EQUIPMENT			
		1XC40 - 1XC44 - 1X15060	
WASHING CYCLES (sec)			
		1 (120)	2 (180)
WATER SUPPLY 55°C			
racks/h(*) ⁽¹⁾		30	20
WATER SUPPLY 10°C			
racks/h(*) ⁽¹⁾		21	20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)			
		2.3 L	
BOILER CAPACITY			
		5.7 L	
BOILER HEATING ELEMENT			
		4500 W	
RINSING TEMPERATURE (SET)			
		85°C	
TANK CAPACITY			
		29 L	
TANK HEATING ELEMENT			
		2700 W	
TANK TEMPERATURE (SET)			
		55°C	
PUMP POWER			
		650 W (340 L/min ^{***})	
DRAIN PUMP (optional)			
		25 W h MAX drainig 0.8m (40 L/min ^{***})	
NOISE			
		63 dB(A)	

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.